


- Be sure to read and understand all instruction sheets completely before beginning assembly or installation.
- All assembly and installation work must be performed by qualified personnel, in accordance with all applicable national and local building and electrical codes.
- Be aware that the weight of some fixtures may exceed the strength rating of the 4" electrical junction box or other such hardware at your site. In all cases, it is the responsibility of the contractor to properly secure the fixture to the structure, and to provide adequate support for the fixture.
- Due to constant production improvements, details of the design, material or finish may change in any way that will not significantly alter installed appearance or reduce function or performance.

FIXTURE BODY ASSEMBLY

>> READ ME FIRST <<



NOTE: to protect the Crystal Lens from possible damage during shipping, this fixture ships partially disassembled.

Carefully stack the components as illustrated. Take care to position the electrical wires into the Notch in the Metal Reflector Plate, and then send the wires toward the middle of the Decorative Cover. Complete the assembly of the Fixture Body with the (4) top screws.

Please refer to the next instruction sheet for fixture installation.

Atlas
LIGHTING & HOME
ARTISTRY THROUGH LIGHTING AND STYLE

ITEM#: CL11439

- Be sure to read and understand all instruction sheets completely before beginning assembly or installation.
- All assembly and installation work must be performed by qualified personnel, in accordance with all applicable national and local building and electrical codes.
- Be aware that the weight of some fixtures may exceed the strength rating of the 4" electrical junction box or other such hardware at your site. In all cases, it is the responsibility of the contractor to properly secure the fixture to the structure, and to provide adequate support for the fixture.
- Due to constant production improvements, details of the design, material or finish may change in any way that will not significantly alter installed appearance or reduce function or performance.

JUNCTION BOX\

1) Turn power off! Pull the wires out of the junction box and feed them through the center hole in the mounting plate.


Attach the mounting plate to the junction box with the screws provided.

2) Connect the light fixture wires to the wires in the junction box.

Wire black or brown to line voltage, white or blue to neutral, and attach the green or bare wire to the green ground screw provided on the mounting plate. Use wire nuts on the connections and leave no bare wire exposed (excepting the green). Tuck the wires inside the junction box leaving the wire connector to come through the hole.

3) Connect the wire connectors from the led boards to the connector coming out of the junction box. Secure the light fixture to the mounting plate by lining up the holes on the decorative cover with the threaded holes on the mounting plate and screwing in the flat head screws provided. Make sure to fasten securely.

4) Turn your power back on and you have completed the installation process.



Atlas
LIGHTING & HOME
ARTISTRY THROUGH LIGHTING AND STYLE

ITEM#: CL11439