

All assembly and installation work must be performed by qualified personnel, in accordance with all applicable national and local building and electrical codes. Be aware that the weight of some fixtures may exceed the strength rating of the 4" electrical junction box or other such hardware at your site. In all cases, it is the responsibility of the contractor to properly secure the fixture to the structure, and to provide adequate support for the fixture. Due to constant production improvements, details of the design, material or finish may change in any way that will not significantly alter installed appearance or reduce function or performance.



ITEM#: WL11145

1) Turn power off! Pull the wires out of the junction box and feed them through the center hole in the mounting plate. Attach the mounting plate to the junction box with the screws provided. The mounting plate can be adjusted so your fixture mounts vertically perpendicular to the ceiling.

2) Attach the diffuser support arm to the decorative plate with the screws on the inside of the decorative plate.

3) Connect the light fixture wires to the wires in the junction box. Wire black or brown to line voltage, white or blue to neutral, and attach the green or bare wire to the green ground screw provided on the mounting plate. Use wire nuts on the connections and leave no bare wire exposed (excepting the green). Tuck the wires inside the junction box.

4) Secure the light fixture to the mounting plate by lining up the holes on the decorative cover with the threaded holes in the mounting plate and screwing in the screws provided. Make sure to fasten securely.

5) Slide the diffuser into the fixture from above until the diffuser sits on the platform under the led light source. Turn on your power and you have completed the installation process.

